



PINATINT

DESCRIPCIÓN

An aqueous dispersion of pigments with anionic and non-anionic tensioactive agents.

VENTAJAS

- ✓ Excellent tinting capacity
- ✓ Mixes into the paint quickly and easily
- ✓ Fully compatible with water-based paints

USOS RECOMENDADOS

For tinting all types of water-based paints; water-based enamels and acrylic varnishes, plastic paint, PVA paint, distemper and whitewash, etc.

PRESENTACIÓN

Colour: see colour chart
50 ML, 250 ML, and 500 ML pots.

CARACTERÍSTICAS TÉCNICAS

Density: 1.15 ± 0.02 Kg./L. (depending on colour)

Maximum recommended concentration, 5%.

APLICACIÓN

Shake well to mix the tint and add to paint as required, mix and stir until thoroughly mixed to attain the desired colour.

Lightfastness depends on the quality of the base paint and the concentration of tint added. If used in exterior spaces, consult the colour chart to select the most UV-resistant colours. All colours can be mixed, creating an infinite range of possible hues.

SEGURIDAD

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com