



ANTI-RUST ENAMEL

DESCRIPCIÓN

A multi surface anti-rust enamel which can be painted directly onto metalwork without priming. Provides excellent resistance to weathering, adheres well to the surface and is tough and long lasting.

VENTAJAS

- ✓ Smooth finish
- ✓ Apply directly to metal
- ✓ Brushes on easily
- ✓ Excellent coverage
- ✓ Resists exteriors well
- ✓ Excellent anti corrosion protection
- ✓ Multi surface adherence

USOS RECOMENDADOS

Anti-rust enamel for industrial and decorative use. Can be applied directly without priming to machinery, structures, steel bars etc.

PRESENTACIÓN

Colours: white and black, satin finish and from our colour chart

Finish: satin

0.75 and 4 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – alkaline resins

Pigments: selected light fast and anti-corrosion pigments

Solvent: blended hydrocarbons

Density: 1.25 ± 0.02 Kg/L. (depending on colour)

Solid volume: 65-70%

Coverage: 10 – 12 m²/Lt per coat

Drying: To the touch 1 hour
Total 3 hours
Repaint 6 hours.

APLICACIÓN

Coats: 2

Recommended thickness: 30-35 micron, dry per coat.

Dilution: 5 % maximum with polyurethane solvent

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use

TRATAMIENTOS DE SUPERFICIES

New surfaces: prepare adequately depending on surface

Wood and plaster: seal first

Metalwork and galvanised steel: no need to prime

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com