



ENAMEL FOR IRONWORK

DESCRIPCIÓN

Metal finish synthetic enamel with excellent adherence and hard wearing colours. Gives a hammered decorative finish. Excellent exterior performance.

VENTAJAS

- ✓ Metal finish
- ✓ Brushes on easily
- ✓ Hard wearing
- ✓ Excellent coverage
- ✓ Excellent anti-corrosion performance

USOS RECOMENDADOS

Pinay ironwork enamel is ideal for painting and protecting all types of iron surfaces: handrails, bars, garden furniture and fixtures, etc.

PRESENTACIÓN

Colours: black, grey, brown, green, blue and gold from the automatic colour mixing system
Finish: hammered
0.375, 0.75 and 4 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – alkaline resins
Pigments: selected light fast pigments
Solvent: blended hydrocarbons

Density: 1.65 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/Lt per coat

Drying:

To the touch	2 hour
Total	6 hours
Repaint	24 hours.

APLICACIÓN

Coats: 2

Dilution: 5-10 % maximum with solvent for synthetic enamels

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

TRATAMIENTOS DE SUPERFICIES

New surfaces: prepare adequately depending on surface

Wood and plaster: seal first

Metalwork: prime with metal primer

Galvanised steel: prime with Pinafix water or solvent-based primer

PVC and plastic: sand lightly and prime with Pinafix solvent-based primer.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com