



SANIES

DESCRIPTION

A coating formulated from acrylic polymers, designed for the decoration, protection and waterproofing of façades.

ADVANTAGES

- ✓ Good breathability.
- ✓ Excellent adhesion to prevent blistering on substrates such as fibre cement, concrete, bricks, mortar, ceramic tiles, etc.
- ✓ Good weather resistance. Withstands exposure to sunlight, cold and rain.
- ✓ Once dry and set, it forms a completely waterproof coating.
- ✓ Good resistance to wet abrasion.
- ✓ Resistant to microorganisms: contains an anti-mould preservative that protects against the formation of mould, algae and mildew.
- ✓ Up to a 5-year guarantee on façades, provided the painting process recommended by Pinay is followed.

RECOMMENDED USES

Particularly suitable for painting all types of building surfaces, such as façades, party walls, light wells, etc., both indoors and outdoors.

PRESENTATION

Colours: White, available in smooth and textured finishes. Matt finish.

Available in 5 kg and 25 kg containers.

TECHNICAL CHARACTERISTICS

Composition: Fixed binder; acrylic polymer resins.

Pigments Titanium dioxide and selected extenders.

Density 1.56 ± 0.02 kg/l. 1.76 ± 0.02 kg/l (rough finish).

Coverage 9–11 m²/litre per coat (Approximate, depending on the surface requirements).

Drying

Touch dry	1–2 hours.
Fully dry	24 hours.
Recoating	After 24 hours at 20 °C.

APPLICATION

Coats 2 or more coats, as required

Thinning 15–30% for the first coat, and up to 10% for subsequent coats.

Application temperature Ambient temperature of 5 to 30 °C.

Application tools Air-spray equipment, airless sprayers, brush, paintbrush, roller, etc.
Stir thoroughly before application.

SURFACE PREPARATION

New surfaces: must be dust-free, clean, dry and free from salt efflorescence.

Existing surfaces: in addition to the above considerations, any remaining paint must be removed. When applying to previously painted surfaces, defective and cracked areas must be sanded down, then filled and levelled using the most suitable product from the Pinayplast range. If the surface is powdery or has significant variations in absorbency, apply an acrylic primer to even out the surface, particularly with intense colours.

CONSERVATION

Easily homogenised by thorough stirring after 12 months' storage in a sealed container. Does not form a skin or clots. Keep away from temperatures below 5 °C.

SAFETY

Refer to the labelling and Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com

