



SILICATE COATING

DESCRIPCIÓN

A coating formulated with potassium silicate emulsion. The product does not form an outer layer on the surface but is absorbed by it, to withstand the most adverse climate conditions. Washable and excellent coverage.

VENTAJAS

- Moisture breathable
- Excellent adherence to mineral surfaces, not suitable for other types of surface
- Excellent weathering. Withstands sunlight, cold and rain
- Once dry and set it forms a completely waterproof layer
- Resistant to wet rubbing

USOS RECOMENDADOS

Ideal for painting mineral finish walls and surfaces, interior and exterior.

PRESENTACIÓN

Colour: white
Finish: matt.
14 l tubs

CARACTERÍSTICAS TÉCNICAS

Composition fixed vehicle: acrylic styrene polymer
Pigments: titanium dioxide and selected extender oils.

Density: 1.44± 0.02 Kg./L

Solid volume: 61 ± 2%

Coverage: 8 – 10 m²/L per coat (Approximately, depending on surface).

Drying	to the touch	1-2 hours.
	Total	24 hours.
	Repaint	After 24 hours at 20 °C.

APLICACIÓN

Coats: 2

Dilution: 15-20 % with water

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use

TRATAMIENTOS DE SUPERFICIES

All new surfaces must be dust free, clean, dry and free of salt bloom.

All new surfaces must be dust free, clean, dry and free of salt bloom, rust, grease or wax, etc. and properly primed. If the surface is in good condition, clean and apply a coat of paint. Mix well before use.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com