



PLIOLITE COATING

DESCRIPTION

A waterproof coating formulated from Pliolite resin. A smooth matt finish, can be applied to any building surface.

ADVANTAGES

- ✓ Excellent adherence to powdery surfaces and surfaces with little absorbency.
- ✓ Excellent weathering. Withstands sunlight, cold and rain.
- ✓ Once dry and set it forms a completely waterproof layer.
- ✓ Resistant to wet rubbing.

RECOMMENDED USES

Ideal for protecting and painting walls and typical exterior building surfaces which are still slightly damp: concrete, mortar, brickwork, plaster, stone, render and fibre cement. Its microporous nature makes it ideal for waterproofing for exteriors which require breathability and permeability to CO₂.

PRESENTATION

Colour: White.

Finish: Matt.

14 and 15 l tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Pliolite resins.

Pigments: Titanium dioxide and selected extender oils.

Density: 1.48± 0.02 Kg./L

Solid volume: 72 ± 2%

Coverage: 8 – 10 m²/L per coat (Approximately, depending on surface).

Drying	to the touch	1-2 hours.
	Total	24 hours.
	Repaint	After 24 hours at 20 °C.

APPLICATION

Coats: 2 or more as necessary

Dilution: 15-30 % first coat and up to 10% for successive coats with white spirit

Application temperature: Between -10 and 35 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com