



ROKIPLAS ROUGH COAT

DESCRIPCIÓN

Rough finish coating formulated from acrylic polymers for exterior decoration and protection of facades and walls. Excellent weatherproofing for the most extreme cases

VENTAJAS

- Good breathability
- Excellent adherence, prevents blistering on surfaces such as fibrocement, concrete, brickwork, mortar, tile, ceramics, etc.
- Weather resistant, withstands sunlight, cold and rain
- Once set and dry it forms a completely waterproof barrier
- Washable and hardwearing

Tested at Laboratorios Geocisa - test report number: P-02/01564

USOS RECOMENDADOS

Ideal for painting all types of building surfaces including facades, walls, patios, etc. Exterior and interior.

PRESENTACIÓN

Colours: white and colour chart, base

Special colours available upon request using the Pinay paint mixer system

Textured finish colours available upon request and from colour chart

Finish: matt

5Kg and 25Kg tub

CARACTERÍSTICAS TÉCNICAS

Composition fixed vehicle: acrylic polymer resins

Pigments: titanium dioxide and selected extender oils.

Density: 1.67± 0.02 Kg/L

Solid volume: 58 ± 2%

Performance: 1Kg/M2 (Approximately, depending on surface requirements).

Drying: To the touch in 1 to 2 hours
Total 24 hours
Repaint After 24 hours at 20 °C

APLICACIÓN

Coats: 2 or more as required

Dilution: 15-30 % first coat and up to 10% for successive coats

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

TRATAMIENTOS DE SUPERFICIES

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com