



ACRYLIC FIXER

DESCRIPTION

Latex-based primer, fixer and waterproofer formulated from acrylic polymers. Ideal for preparing porous surfaces including lime, cement, distemper etc.

ADVANTAGES

- ✓ Forms waterproof barrier which penetrates the surface deeply.
- ✓ Protects by forming a film against inclement weather.
- ✓ Reduces staining from soluble salts.
- ✓ Impermeable to rainwater but breathable to water vapour.

RECOMMENDED USES

Ideal for sealing surfaces of cement, render, plaster, etc.

PRESENTATION

Colour: Colourless.

Finish: Satin.

1, 5 and 15l tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Acrylic copolymers in emulsion.
Solvent: Water.

Density: 1.02 ± 0.02 Kg/L.

Coverage: 10 m²/Lt. (diluted with water)

Drying: To the touch in 30 minutes
Repaint after 12 hours at 20 °C.

APPLICATION

Coats: 1

Dilution: 1 litre of acrylic fixer to 5 litres of water.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com