



UNION BRIDGE

DESCRIPTION

Primer formulated from aqueous copolymers with selected fine aggregates and minerals. Use as a bonding layer between different materials.

ADVANTAGES

- ✓ Highly penetrating.
- ✓ Interior and exterior use.
- ✓ Excellent mechanical properties, tough and hardwearing.
- ✓ Textured finish.
- ✓ Recommended for non-absorbing surfaces.

RECOMMENDED USES

Ideal as a bonding coat on tiles, floated concrete, plaster, super fine plaster, single coats, cement and plastic paints, etc.

PRESENTATION

Colour: Yellow.
Finish: Matt
1, 5 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle: Acrylic resins.
Pigments: Ochre and selected extender oils.

Density: 1.53 ± 0.02 Kg./L.

pH 7.5-8.5

Coverage: 230-280 gr/ m² (Approximately).

Drying: to the touch 30 minutes
Total 24 hours
Can be worked on after 5 hours, although 24 hours is recommended.

APPLICATION

Coats: 1

Dilution: Dilute with water 5 %.

Application temperature: 5 to 30° C.

Tools: Brush or roller.

SURFACE PREPARATION

Surface preparation: must be free from dust and salt bloom, and be clean and dry.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com