



## SEALANT

### DESCRIPTION

A sealing primer for use on all porous surfaces such as plaster and wood.

### ADVANTAGES

- ✓ Excellent adherence and coverage.
- ✓ Easy to apply.
- ✓ Easy to apply and sand.
- ✓ Excellent sealing properties.

### RECOMMENDED USES

Ideal for use on all types of porous surfaces which are difficult to paint: brickwork, plaster, surfaces affected by salt, stains from smoke or grease, new woodwork, etc. after priming, paint over with plastic paint or synthetic enamel.

### PRESENTATION

Colour: White.

Finish: Matt.

0.75, 4 and 15 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition:** Fixed vehicle: Synthetic resin.  
Pigment: Titanium dioxide.  
Solvent: Blend of hydrocarbons.

**Density:** 1.62 ± 0.02 Kg/L.

**Performance:** 10-12 m<sup>2</sup>/Lt.

**Drying:** to touch 30 minutes.  
Total 60 minutes.  
Repaint: after 24 hours at 20 °C.

## APPLICATION

**Coats:** 1 or 2 depending on porosity.

**Dilution:** 10-15 % for spraying.  
5-10 % for brushing or rolling.

**Application temperature:** Between 5 and 30 °C.

**Painting tools:** Spray gun, airless, wide brush, narrow brush, roller, etc.  
Shake vigorously before use.

## SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range.

## STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

## SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com