



WATER-BASED ANTI-STAIN TREATMENT

DESCRIPCIÓN

Water-based thixotropic paint, almost odourless. Ideal for covering difficult stains left by damp, marker pens, grease, nicotine, etc.

VENTAJAS

- ✓ Excellent coverage, sealing and priming capabilities
- ✓ Excellent stain sealing
- ✓ Ideal for ceilings and walls, non-drip
- ✓ Washable
- ✓ Extraordinary whiteness, does not yellow

USOS RECOMENDADOS

Formulated for kitchen ceilings and walls, bathrooms, bars, restaurants and public spaces and workshops where nicotine, grease, smoke or soot stains appear.

PRESENTACIÓN

Colour: white.

Finish: silk matt

0.75 L, 4 L and 12 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – pliotech resin
Pigments: titanium dioxide
Solvent: water

Density: 1.50 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/Lt.

Drying: To the touch in 30 minutes
Total 24 hours
Repaint After 12 hours at 20 °C.
Repaint with plastic paint 2 days.

APLICACIÓN

Coats 1 or 2 depending on the stain

Dilution: 5-10 % with water

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

TRATAMIENTOS DE SUPERFICIES

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery with different levels of absorption, apply a first coat diluted 35-45%, to help bonding.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com