



ANTI-HUMIDITY PAINT

DESCRIPCIÓN

Decorative waterproofing paint, matt finish, ideal for areas where moisture is a problem

VENTAJAS

- ✓ Easy to apply
- ✓ Tough finish
- ✓ Forms a barrier to prevent humidity
- ✓ Can be applied to slightly damp surfaces
- ✓ Excellent washability
- ✓ Made with Pliolite resins
- ✓ Interior and exterior use
- ✓ Resists mould

USOS RECOMENDADOS

Ideal paint for treating humidity caused by filtration and condensation.

Eliminates unsightly staining on walls

Apply to cement, plaster, stone, brickwork, etc. even if still damp. Ideal for ceilings and walls in garages, basements, car parks etc.

PRESENTACIÓN

Colour: white

Finish: matt

0.75 L, 4 L and 15 L tubs

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – Pliolite resin

Pigments: titanium dioxide

Solvent: blended hydrocarbons

Density: 1.65 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/L, single coat

Drying: Total 1 hour
Repaint: Min. 12 hours

APLICACIÓN

Coats 1 or 2

Dilution: 5-10 % with polyurethane solvent

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake well before use.

TRATAMIENTOS DE SUPERFICIES

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery with different levels of absorption, apply a first coat Pinay Pliolite Bonder.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.