



PINALUX SYNTHETIC ENAMEL

DESCRIPCIÓN

Synthetic, high gloss enamel paint, with long-lasting colours. Hard wearing, ideal for outdoor use.

VENTAJAS

- ✓ Hard wearing colour and shine
- ✓ The white and light colours are resistant to yellowing
- ✓ Brushes on easily
- ✓ Excellent coverage
- ✓ Smooth finish
- ✓ Flexible to withstand surface expansion and contraction
- ✓ Resists weathering

USOS RECOMENDADOS

Gloss synthetic enamel paint for interior and exterior use on metal, wood and other properly prepared, sanded and primed surfaces, for a decorative finish.

PRESENTACIÓN

Colours: white and black, matt and satin and from our colour chart. D and TR.
0,375, 0.75 and 4 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle - alkaline resins
Pigments: selected light fast pigments
Solvent: blended hydrocarbons

Density: 1.05 ± 0.02 Kg/L. (depending on colour)

Solid volume: 65-70% depending on colour

Coverage: 10 – 12 m²/Lt, per coat

Drying: to the touch 2 hours
Total 6 hours
Repaint minimum 24 hours.

APLICACIÓN

Coats: 2

Recommended thickness: 30-35 micron, dry per coat.

Dilution: 5 % maximum with solvent for synthetic enamels

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use

TRATAMIENTOS DE SUPERFICIES

New surfaces: prepare adequately depending on surface

Wood and plaster: seal first

Metalwork: prime with metal primer

Galvanised steel: prime with Pinafix water or solvent-based primer

PVC and plastic: sand lightly and prime with Pinafix solvent-based primer

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com