



RUST CONVERTER

DESCRIPCIÓN

Water-based primer to treat rust on iron and steel.
Reacts with the rust to form a layer that protects the metal underneath.

VENTAJAS

- ✓ Transforms rust into a protective layer
- ✓ Paint over with enamel
- ✓ Saves sanding the entire surface, just remove flaky rust
- ✓ Apply directly over the rust

USOS RECOMENDADOS

Ideal for all types of components made from iron or steel, including window frames, doorframes, handrails and electrical appliances and vehicles.

PRESENTACIÓN

Colour: white, turning black on reaction

0.25 and 0.50 L tubs.

CARACTERÍSTICAS TÉCNICAS

Density: 1.00 ± 0.02 Kg./L.

Reaction time: 15-30 minutes.

Drying: To the touch 30-45 minutes
Repaint after 6 hours (under normal temperature and humidity)

Coverage: 8-10 m² / L.

APLICACIÓN

Coats: 1

Dilution: ready to use

Application temperature: 5 to 30 °C.

Tools: Blade, brush, roller

Surface preparation:

Remove dirt and grease before treatment by washing with warm soapy water or solvent if required, rinse and dry. Remove loose and flaky paint and rust.

How to use:

Shake well. Pour the required amount into a separate container and close the original container to protect the product's reactive qualities.

Pinay Rust Converter can be painted over rust with a brush without dilution, working it well into difficult areas. A chemical reaction will begin to appear as Rust Converter works, transforming the rust into a black layer of iron salts. If an area does not react, wash and degrease again and apply a second coat.

SEGURIDAD

Consult label and product safety data sheet



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com