



URETHANE LACQUER

DESCRIPCIÓN

Urethane lacquer is a single-component, polyurethane-based satin enamel. It gives a high quality silky lacquered finish to a surface.

VENTAJAS

- ✓ Retains colour and shine
- ✓ Colours do not yellow
- ✓ Easy to brush on
- ✓ Excellent coverage
- ✓ Dries smooth
- ✓ Flexible to natural contraction and expansion
- ✓ Resists weathering
- ✓ Anti-rust
- ✓ Adheres to multiple surfaces

USOS RECOMENDADOS

Satin synthetic enamel for interior and exterior use on metal, wood and other properly prepared, sealed and primed surfaces, when a highly decorative finish is required. Appropriate for marine uses when prepared adequately.

PRESENTACIÓN

Colours: white and black and colours from the automatic paint mixer chart, D and TR
Finish: satin and matt
0.75 and 4 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – modified alkaline resins

Pigments: titanium dioxide

Solvent: blended hydrocarbons

Density: 1.30 ± 0.02 Kg/L.

Coverage: 10 – 12 m²/Lt single coat

Drying: to the touch 30 minutes
Total 6 hours
Repaint minimum 12 hours

APLICACIÓN

Coats: 2

Recommended thickness: 30-35 microns per coat

Dilution: 5 % maximum with polyurethane solvent

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

TRATAMIENTOS DE SUPERFICIES

Surfaces should be clean, dry and free of dust, grease and rust. When painting on wood or plaster, apply a coat of sealant first.

Can be applied directly to metal, PVC, galvanised steel and plastic but we recommend testing on a small area first to ensure it adheres correctly.

Surfaces exposed to marine and extreme environments, always apply two coats of dual-component anti rust epoxy primer, to a thickness of between 100-120 microns. Then apply two coats of Pinay urethane lacquer for interior use and three coats for exteriors.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com