



PINAFIX SOLVENT-BASED PRIMER

DESCRIPCIÓN

Multiuse primer which forms a bond to paint non-absorbent surfaces.

VENTAJAS

- ✓ Excellent adherence
- ✓ Easy to apply
- ✓ For exterior use too
- ✓ Excellent coverage
- ✓ Brushes on easily and smoothly

USOS RECOMENDADOS

Primer for metal including iron, aluminium, galvanised steel, copper, zinc, etc. also PVC and plastic surfaces.

Can be overpainted with synthetic enamel, urethane lacquer etc.

PRESENTACIÓN

Colours: white
0.75 and 4 L tubs

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – alkaline resins

Pigments: titanium dioxide and selected extender oils

Solvent: blended hydrocarbons

Density: 1.35 ± 0.02 Kg/L.

Coverage: 1– 10 m²/Lt, one coat

Drying: to the touch 2 hours

Total 24 hours

Repaint: minimum 24 hours.

APLICACIÓN

Coats: 1 or 2

Dilution: 10-15 % maximum with solvent for synthetic enamel

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

TRATAMIENTOS DE SUPERFICIES

Ensure surfaces are clean, dry and free of rust, dust, salt bloom, flaky paint, grease and wax. To ensure maximum rust prevention, make sure there is no dirt on the surface to be painted. PVC and plastic: sand lightly and prime with Pinay solvent-based primer.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com