



LASUR MATT AND SATIN VARNISH

DESCRIPCIÓN

Lasur wood protector is formulated from solvent-based resins to protect and enhance exterior and interior woodwork.

VENTAJAS

- ✓ Excellent water repellent properties
- ✓ Excellent protection from UV rays
- ✓ Lets wood breathe
- ✓ Transparent, to let the natural beauty of wood show through

USOS RECOMENDADOS

For protecting all types of woodwork requiring a hardwearing attractive finish. The varnish provides a protective coating for interior and exterior woodwork.

PRESENTACIÓN

Clear and automatic paint mixer colours
Finish: satin and gloss
0.75 and 4 L tubs

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – urethane/alkyd-based resins

Solvent: aliphatic hydrocarbons

Density: 1.02 ± 0.02 Kg./L.

Coverage: 13 – 15 m²/Lt.

Drying: to the touch 2 hours
Repaint after 24 hours at 20 °C.

APLICACIÓN

Coats: 2.

Dilution: ready to use

Application temperature: 5 to 30 °C.

Tools: spalter, brush, roller.

Method:

Shake well before use. Do not dilute and apply the first coat along the grain. After 24 hours, sand and apply second coat.

Colour tone varies with the number of coats, dilution, absorption and colour of wood.

TRATAMIENTOS DE SUPERFICIES

New woodwork: sand, remove dust and ensure the wood is dry. If better protection is needed against mould or wood boring insects, treat with the appropriate product. Do not use on tropical hardwoods.

Varnished wood: sand and apply a coat of varnish, diluted 5%. Peeling varnish must be removed with stripper and then treated as new wood. If the nature of the old varnish is unknown, test first for compatibility.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com