



SATIN FINISH PRIMER

DESCRIPCIÓN

Quick-drying satin finish synthetic primer for industrial use.

VENTAJAS

- ✓ Excellent adherence to iron
- ✓ Short drying and repainting times
- ✓ Anti-corrosive properties
- ✓ Brushes on easily and smoothly
- ✓ Satin finish

USOS RECOMENDADOS

For workshop or site use where structures require temporary protection until final painting.

PRESENTACIÓN

Colour: red, grey, black
Finish: satin
4 and 15 L tubs.

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – synthetic resins
Pigments: chromate-free antioxidants and selected extender oils
Solvent: blended hydrocarbons.

Density: 1.40 ± 0.02 Kg/L. satin finish

Solid volume: 60% satin finish

Coverage: 8 – 10 m²/Lt. satin finish

Drying: to the touch 20 minutes
Total 60 minutes
Repaint: after 3 hours at 20 °C.

APLICACIÓN

Coats: 1 or 2, according to requirements

Recommended thickness: 25-30 microns dry.

Dilution: 10-15 % for spraying or air-less.
5-10 % for brushing or rolling

Application temperature: 5 a 30 °C.

Tools: spray gun, airless, brush or roller, etc.
Shake well before use.

TRATAMIENTOS DE SUPERFICIES

Surface preparation:

Eliminate rust by blasting or sanding. The surface must be free of grease and be dry and clean of anything which may impede the adherence of the primer.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.
This primer is only for industrial use

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com