



SHOP PRIMER

DESCRIPCIÓN

Phosphating primer, single component with phosphoric acid for ferrous and non-ferrous surfaces (aluminium, galvanised steel, etc.) for industrial use.

VENTAJAS

- ✓ Excellent adherence to all types of metal
- ✓ Can be painted over in a variety of finishes
- ✓ Short drying and repainting times
- ✓ Accepts soldering and oxyacetylene torch cutting
- ✓ Contains non-toxic anticorrosive pigments
- ✓ Temporary protection for recently shot-blasted steel

USOS RECOMENDADOS

Specially formulated for applying to ferrous and non-ferrous surfaces (galvanised, aluminium, zinc, etc.), which present difficult adherence. As a pre-treatment for sand blasted steel, accepts different finishes (alkyd, polyurethane, epoxy, etc.).

PRESENTACIÓN

Colours: white or clear
Finish: matt
4 and 15 L tubs

CARACTERÍSTICAS TÉCNICAS

Composition: fixed vehicle – modified butyl polyvinyl resin
Pigments: chromate-free antioxidant and selected extender oils
Solvent: blended hydrocarbons, alcohols and acetone

Density: 1.02 ± 0.02 Kg./L.

Solid volume: 32 ± 2%

Coverage: 13 – 18 m²/Lt. (Approx. per coat when sprayed on).

Drying: to the touch 15 minutes
Total 30 minutes
Repaint: after 3 hours at 20 °C.

APLICACIÓN

Coats: 1

Recommended thickness: 10 - 15 microns dry

Dilution: 10 % for spray gun with solvent
5-10 % for brush or roller.

Application temperature: 5 to 30 °C.

Painting tools: spray gun, brush, roller, etc.
Mix well before use.

TRATAMIENTOS DE SUPERFICIES

Surfaces should be clean, dry and sound, and free from grease, dust and rust. Eliminate any deposit which may affect adherence by abrasive stripping.

CONSERVACIÓN

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 0 °C.

SEGURIDAD

Consult the label and the Safety Data Sheet.
Priming only appropriate for industrial uses.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com