



DELUXE PREMIUM MINERAL

DESCRIPTION

High-quality vinyl emulsion paint with excellent resistance to scuffing and an extra-matt white finish. Perfect, seamless finishes providing maximum coverage.

ADVANTAGES

- ✓ Vinyl Paint
- ✓ Ideal for plasterboard and sprayed plaster surfaces; can be applied directly without priming.
- ✓ Good breathability.
- ✓ Easy to apply.
- ✓ Deep matt finish.
- ✓ Excellent coverage even when thinned.
- ✓ Excellent adhesion.
- ✓ Washable.
- ✓ Does not yellow.

RECOMMENDED USES

Particularly suitable for decorating vertical surfaces such as cement, plaster, brick, concrete, plasterboard and gypsum, where a top-quality finish with the highest performance is required.

PRESENTATION

Colour: White.

Matt finish.

12-pack formats

TECHNICAL CHARACTERISTICS

Composition: Fixed binder; selected vinyl copolymers.

Pigments

Titanium dioxide and inorganic pigments.

Solvent

Water.

Density 1.55 ± 0.02 kg/l, depending on the colour.

V. Solids 44.46 ± 2%
Solids by weight 61.20 ± 2%
% VOC: 0
VOC: 0 g/l

Coverage: 10–12 m²/litre (Approximate and depending on the substrate).

Drying To the touch 30 minutes.
Recoating After 4 hours at 20 °C. Fully
dry 24 hours.

Wet scrub resistance: Class 2 according to standard UNE-EN 13300:2001.

APPLICATION

Coats 2 coats

Thinning 15–30% with water.

Application temperature Ambient temperature of 5 to 30 °C.

Application tools: Airless spray equipment, brush, paintbrush, roller,
etc.
Stir thoroughly before application.

SURFACE PREPARATION

New surfaces: must be dust-free, clean, dry and free from salt efflorescence.

Existing surfaces: in addition to the above considerations, any remaining paint must be removed. When applying to previously painted surfaces, defective and cracked areas must be sanded down, then filled and levelled using the most suitable product from the Pinayplast range. If the surface is old, highly porous, sandy and unstable, or exhibits significant variations in absorbency, apply an acrylic primer to even out the surface, particularly when using intense colours.

CONSERVATION

Easy to homogenise by simple stirring after 12 months' storage in a sealed container. Does not form a skin or clots. Keep away from temperatures below 5 °C.

SAFETY

Refer to the labelling and Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com