



MATE R-CRIL

DESCRIPTION

High-quality, high-coverage matt emulsion paint formulated from acrylic polymers, designed for decorating, protecting and waterproofing walls.

ADVANTAGES

- ✓ Good breathability.
- ✓ High whiteness.
- ✓ Excellent weather resistance. Withstands exposure to sunlight, cold and rain.
- ✓ High resistance to wet scrubbing.
- ✓ High coverage
- ✓ Does not yellow.
- ✓ Extra matt.
- ✓ Washable.
- ✓ Complies with Directive 2004/42/EC on volatile organic compounds (VOCs).

RECOMMENDED USES

Particularly suitable for decorating vertical surfaces (plaster, cement, render, wood, etc.), where a high-quality, high-performance finish is required; its matt finish helps to minimise imperfections on smooth walls.

PRESENTATION

Colour: White, matt finish.

Available in 0.750 L, 4 L and 14 L sizes.

TECHNICAL CHARACTERISTICS

Composition Binder: Acrylic polymer resins. Pigments Titanium dioxide and selected extenders.

Density	1.52 ± 0.02 kg/l
----------------	------------------

% Solids by weight $60 \pm 2\%$

% V. Solids $40 \pm 2\%$

Coverage 10–12 m²/litre per coat (Approximate, depending on the surface requirements).

Drying:

To touch:	30 minutes.
Fully	24 hours.
Repainting	6–12 hours

Wet abrasion resistance: Class 2 in accordance with standard UNE-EN 13300:2001 (Test carried out by Geocisa)

APPLICATION

Coats 2 or more coats, as **required**. **Dilution:**

10–20% for the first coat, and up to 10% for subsequent coats.

Dilution 10–20% for the first coat, and up to 10% for subsequent coats.

Application temperature Ambient temperature of 5 to 30 °C.

Application tools Airless spray equipment, brush, paintbrush, roller, etc.
Stir thoroughly before application.

SURFACE PREPARATION

New surfaces: must be dust-free, clean, dry and free from salt efflorescence.

Existing surfaces: in addition to the above considerations, any remaining paint must be removed. When applying to previously painted surfaces, defective and cracked areas must be sanded down, then filled and levelled using the most suitable product from the Pinayplast range. If the surface is powdery or has significant variations in absorbency, apply an acrylic primer to even out the surface, particularly with intense colours.

CONSERVATION

Easy to homogenise by simple stirring, even after 12 months' storage in a sealed container. Does not form a skin or clots. Keep away from temperatures below 5 °C.

SAFETY

Refer to the labelling and Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com