



EXTRA SUPER



DESCRIPTION

High quality water-based plastic paint formulated with vinyl copolymers in emulsion. Excellent coverage for interior and exterior vertical walls.

ADVANTAGES

- ✓ Excellent adherence to all sorts of building materials.
- ✓ Good breathability.
- ✓ Easy to apply.
- ✓ Excellent coverage.
- ✓ Non-drip.

RECOMMENDED USES

Ideal for painting interior walls (plaster, cement, render, wood, etc.) where a high quality high performance finish is required. Its matt finish reduces faults in smooth walls.

PRESENTATION

Colour: white.

Available in paint mixing machine D and TR.

Finish: matt.

0.75, 4, 10 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Selected vinyl copolymers.

Pigments: Titanium dioxide and organic and non-organic pigments.

Solvent: Water.

Density: $1.58 \pm 0.02 \text{ Kg/L}.$

Coverage: 10 – 12 m2/Lt (Approximately, depending on surface).

Drying: To the touch in 60 minutes.

Total 24 hours.

Repaint After 24 hours at 20 °C.

APPLICATION

Coats: 2

Dilution: 15-30 % with water.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 $^{\circ}$ C.

SAFETY

Consult the label and the Safety Data Sheet.

