



## PINAYPLUS



### DESCRIPTION

Good quality water-based plastic paint, matt white. Formulated with vinyl copolymers in emulsion. Excellent coverage for interior and exterior vertical walls.

### ADVANTAGES

- ✓ Excellent adherence to all sorts of building materials.
- ✓ Good breathability .
- ✓ Easy to apply.
- ✓ Excellent coverage.
- ✓ Does not yellow.
- ✓ Supermatt finish.

### RECOMMENDED USES

Ideal for painting interior walls (plaster, cement, render, wood, etc.) where a high quality high performance finish is required. Its matt finish reduces faults in smooth walls.

### PRESENTATION

Colour: White

Finish: Matt

0.75, 4, and 15 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition** Fixed vehicle: Selected vinyl copolymers.

Pigments: titanium dioxide and organic and non-organic pigments

Solvent: Water.

**Density:** 1.52 ± 0.02 Kg/L.

**Solid volume:** 58 ± 2%.

**Volatile Organic Compounds (VOC):** EU limit category (A/a) 30 gr/l.  
The product has a VOC count of 8 gr/ l.

**Coverage:** 10 – 12 m<sup>2</sup>/Lt (Approximately, depending on surface).

**Drying:** To the touch in 60 minutes.  
Total 24 hours.  
Repaint After 24 hours at 20 °C.

## Tests

### ~~S/UNE- ISO 1542.~~

- Fineness = 30 .

### ~~S/UNE- ISO 11998. Wet rub resistance test S/UNE-ISO 11998.~~

Loss of dry film thickness = 4.

### ~~S/UNE- ISO 6504-3. Coverage performance and contrast percentage. S/UNE-ISO 6504-3.~~

- Contrast percentage 98 %.
- Non-volatile material content 56.8 % by mass.

## APPLICATION

**Coats:** 2

**Dilution:** 15-30 % with water.

**Application temperature:** Between 5 and 30 °C.

**Painting tools:** Spray gun, airless, wide brush, narrow brush, roller, etc.  
Shake vigorously before use.

## SURFACE PREPARATION

**All new surfaces** must be dust free, clean, dry and free of salt bloom.

**For old surfaces**, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

## STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

## SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com