

WATER-BASED ENAMEL FOR WALLS 🛛 🏠 と 🔅 🗞

DESCRIPTION

High quality acrylic matt enamel, formulated with acrylic emulsion. Ideal for walls.

ADVANTAGES

- \checkmark High white.
- ✓ Easy to apply.
- ✓ Good weathering.
- \checkmark Excellent coverage.
- ✓ Brushes on easily and smoothly.
- ✓ Excellent adherence to most surfaces (gloss and satin).
- ✓ Does not yellow.
- ✓ Odour-free.

RECOMMENDED USES

Gloss or satin enamel for interior and exterior use on metalwork, wood and other wellprepared, sealed and primed surfaces when a highly decorative finish is required.

PRESENTATION

Colours: White matt finish. Available in paint mixing machine D and TR. 0.75, 4 and 12 l tubs

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Water-based acrylic resins.

	Pigments: Solvent:	Titanium dioxide and selected extender oils. Water.	
Density:	1.26 ± 0.02 Kg/L.		
Coverage:	9 – 10 m2/Lt, hand painted.		
Drying:	To the touch in 2 hours. Total 24 hours. Repaint After 24 hours.		

APPLICATION

Coats:

1 or 2.

Dilution: 10-15 % maximum, with water.

Application temperature: Between 5 and 30 °C.

Painting tools:Spray gun, airless, wide brush, narrow brush, roller, etc.Shake vigorously before use.

SURFACE PREPARATION

New surfaces: prepare depending on the type of material being painted. Wood and plaster: apply sealant first.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l. P.l. San José, s/n / 46812 Ayelo de Malferit / Valencia / Spain t. 96 236 02 92 / f. 96 236 06 01 pinturaspinay.com info@pinturaspinay.com