



ECOLOGICAL



DESCRIPTION

Plastic water-based paint formulated from high-strength acrylic resins. Good opacity and good coverage.

ADVANTAGES

- ✓ Ecological matt plastic paint: complies with ISO 14021.
- ✓ Eco label test carried out by CIDEMCO (DOCE 202/739/CE).
- ✓ Good breathability.
- ✓ High White.
- ✓ Good resistance to wet rubbing.
- ✓ Odour-free.

RECOMMENDED USES

Ideal for painting interior walls (plaster, cement, render, wood, etc.), where easy application, good opacity and washability are required.

PRESENTATION

Colour: white and as a base for paint mixing.

Finish: matt.

0.75, 4 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Acrylic styrene resins.

Pigments: Titanium dioxide and selected extender oils.

Density: 1.54 ± 0.02 Kg/L.

Solid volume: 65 ± 2%.

Coverage: 10 – 12 m²/Lt (Approximately, depending on surface).

Drying: To the touch in 60 minutes
Total 24 hours
Repaint After 24 hours at 20 °C

APPLICATION

Coats: 2

Dilution: 15-30 % with water.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com