



TEXTURED



DESCRIPTION

For interior artex finish. Apply with spraygun or sponge roller.

ADVANTAGES

- ✓ Excellent adherence.
- ✓ Good breathability .
- ✓ Easy to apply
- ✓ Different effects
- ✓ Does not yellow.

RECOMMENDED USES

Ideal for painting walls (plaster, cement, render, wood, etc.). Easy to create a range of decorative finishes: artex, relief, stipple, etc.

For exterior use, if protected with a coat of exterior paint.

PRESENTATION

Colour: White

Finish: Matt.

5 kg and 25 kg tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Copolymers in emulsion.

Pigments: Titanium dioxide and selected extender oils.

Solvent: Water .

Density: 1.70 ± 0.02 Kg/L

Coverage: 1 - 2 m²/L, hand applied

Drying: 4-6 hours.

Repaint: After 24 hours at 20 °C.

APPLICATION

Apply a good plastic paint as a base and top coat

Recommended thickness: Depending on desired finish

Dilution: Dilute with 5% water for roller application, and for spraygun depending on the desired texture, do not dilute or maximum 5% water.

Application temperature: Between 5 and 30 °C.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com