



## DELUXE SINGLE COAT



### DESCRIPTION

High-performance plastic water-based paint formulated with acrylic resins. Excellent quality and coverage.

### ADVANTAGES

- ✓ Plastic Paint, high coverage.
- ✓ Good breathability.
- ✓ High white.
- ✓ Ideal for interior decoration.
- ✓ Washable.

### RECOMMENDED USES

Plastic paint for painting interior walls (plaster, cement, render, etc.), where good coverage is required. Ideal for interior decoration, available in a wide range of colours.

### PRESENTATION

Colours: White and colour chart.  
Finish: Matt.  
0.75 and 4 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition** Fixed vehicle: Acrylic styrene resins.  
Pigments: Titanium dioxide, pigments and selected extender oils.

**Density:** 1.61 ± 0.02 Kg/L.

**Solid volume:** 63 ± 2%.

**Coverage:** 8 – 10 m<sup>2</sup>/L (Approximately).

**Drying**  
To the touch in 60 minutes  
Total 24 hours  
Repaint After 24 hours at 20 °C.

## APPLICATION

**Coats:** 2

**Dilution:** 15-30 % with water.

**Application temperature:** Between 5 and 30 °C.

**Painting tools:** Spray gun, airless, wide brush, narrow brush, roller, etc.  
Shake vigorously before use.

## SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

## STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

## SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com