



SATIN EXTRA



DESCRIPTION

Plastic water-based satin paint formulated with vinyl copolymers in emulsion, for a high quality finish on interior and exterior walls.

ADVANTAGES

- ✓ Excellent adherence to most building materials.
- ✓ Good breathability .
- ✓ Easy to apply.
- ✓ Excellent coverage.
- ✓ Does not yellow.
- ✓ High-satin finish.

RECOMMENDED USES

Ideal for vertical walls (plaster, cement, render, etc.) where a high quality finish is required.

PRESENTATION

Colour: White

Finish: Satin

0.75 L , 4 L, 10 L , 14 L and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Selected vinyl copolymers.
Pigments: Titanium dioxide and organic and inorganic pigments.
Solvent: Water.

Density: 1,25 ± 0.02 Kg/L.

Coverage: 10 - 12 m²/L (Approximately, depending on surface).

Drying To the touch in 30 minutes
Total 24 hours
Repaint After 24 hours at 20 °C.

APPLICATION

Coats: 2

Dilution: 15-20 % with water

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com