

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 1 of 14

Print date: 29/10/2020

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name: 27.- ADITIVO ANTIMOHO
Product Code: VFP

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Not available.

1.3 Details of the supplier of the safety data sheet.

Company: **PINTURAS AYELENSES, S.L.**
Address: POLÍGONO SAN JOSÉ, S/N
City: AIELO DE MALFERIT
Province: VALENCIA
Telephone: 962360292
Fax: 962360601
E-mail: info@pinturaspinay.com
Web: www.pinturaspinay.com

1.4 Emergency telephone number: 962360292 (Only available during office hours; Monday-Friday; 08:00-18:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EU) No 1272/2008:

Acute Tox. 4 : Harmful if swallowed.

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.

Carc. 2 : Suspected of causing cancer.

Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EU) No 1272/2008:

Pictograms:



Signal Word:

Warning

H statements:

H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.

P statements:

P201	Obtain special instructions before use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P321	Specific treatment (see ... on this label).
P391	Collect spillage.
P501	Dispose of contents/container to ...

EUH statements:

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 2 of 14

Print date: 29/10/2020

EUH208 Contains reaction mass of: 5-chloro-2methyl-4isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H - isothiazol-3one [EC no. 220-239-6] (3:1); reaction mass of: 5chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-4-isothiazolin-3one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

Contains:

octhilinone (ISO),2-octyl-2H-isothiazol-3one

diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea

2.3 Other hazards.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.

Not Applicable.

3.2 Mixtures.

Substances posing a danger to health or the environment in accordance with the Regulation (EC) No. 1272/2008, assigned a Community exposure limit in the workplace, and classified as PBT/vPvB or included in the Candidate List:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	specific concentration limit
Index No: 006-015-00-9 CAS No: 330-54-1 EC No: 206-354-4 Registration No: 01-2119517622-45-XXXX	[1] diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea	1 - 2.5 %	Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 (M=10) - Carc. 2, H351 - STOT RE 2 *, H373 **	-
CAS No: 1332-58-7 EC No: 310-194-1	[1] Kaolin	0 - 2.5 %	-	-
Index No: 603-001-00-X CAS No: 67-56-1 EC No: 200-659-6 Registration No: 01-2119433307-44-XXXX	[1] methanol	0.1 - 3 %	Acute Tox. 3 *, H311 - Acute Tox. 3 *, H331 - Acute Tox. 3 *, H301 - Flam. Liq. 2, H225 - STOT SE 1, H370 **	STOT SE 1, H370: C ≥ 10 % STOT SE 2, H371: 3 % ≤ C < 10 %
Index No: 603-027-00-1 CAS No: 107-21-1 EC No: 203-473-3 Registration No: 01-2119456816-28-XXXX	[1] ethanediol, ethylene glycol	0 - 2.5 %	Acute Tox. 4 *, H302	-

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 3 of 14

Print date: 29/10/2020

Index No: 613-112-00-5 CAS No: 26530-20-1 EC No: 247-761-7 Registration No: 01-2120768921-45-XXXX	octhilinone (ISO),2-octyl-2H-isothiazol-3one	0.05 - 0.25 %	Acute Tox. 3 *, H311 - Acute Tox. 3 *, H331 - Acute Tox. 4 *, H302 - Aquatic Acute 1, H400 (M=10) - Aquatic Chronic 1, H410 (M=1) - Skin Corr. 1B, H314 - Skin Sens. 1, H317	Skin Sens. 1, H317: C ≥ 0,05 %
CAS No: 14808-60-7 EC No: 238-878-4	[1] Quartz (SiO ₂)	0 - 2.5 %	-	-
Index No: 011-002-00-6 CAS No: 1310-73-2 EC No: 215-185-5 Registration No: 01-2119457892-27-XXXX	[1] sodium hydroxide, caustic soda	0 - 0.5 %	Skin Corr. 1A, H314	Skin Corr. 1A, H314: C ≥ 5 % Skin Corr. 1B, H314: 2 % ≤ C < 5 % Skin Irrit. 2, H315: 0,5 % ≤ C < 2 % Eye Irrit. 2, H319: 0,5 % ≤ C < 2 %
CAS No: 8002-74-2 EC No: 232-315-6 Registration No: 01-2119488076-30-XXXX	[1] Paraffin waxes and Hydrocarbon waxes	0 - 2.5 %	-	-
Index No: 605-001-00-5 CAS No: 50-00-0 EC No: 200-001-8 Registration No: 01-2119488953-20-XXXX	[1] formaldehyde	0 - 0.1 %	Acute Tox. 3 *, H311 - Acute Tox. 3 *, H331 - Acute Tox. 3 *, H301 - Carc. 1B, H350 - Muta. 2, H341 - Skin Corr. 1B, H314 - Skin Sens. 1, H317	Skin Corr. 1B, H314: C ≥ 25 % Skin Irrit. 2, H315: 5 % ≤ C < 25 % Eye Irrit. 2, H319: 5 % ≤ C < 25 % STOT SE 3, H335: C ≥ 5 % Skin Sens. 1, H317: C ≥ 0,2 %
Index No: 613-167-00-5 CAS No: 55965-84-9	reaction mass of: 5-chloro-2methyl-4isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-2H - isothiazol-3one [EC no. 220-239-6] (3:1), reaction mass of: 5chloro-2methyl-4-isothiazolin-3-one [EC no. 247-500-7]and 2-methyl-4-isothiazolin-3one [EC no. 220-239-6] (3:1)	0 - 0.0015 %	Acute Tox. 2, H310 - Acute Tox. 2, H330 - Acute Tox. 3, H301 - Aquatic Acute 1, H400 (M=100) - Aquatic Chronic 1, H410 (M=100) - Eye Dam. 1, H318 - Skin Corr. 1C, H314 - Skin Sens. 1A, H317	Skin Corr. 1C, H314: C ≥ 0,6 % Skin Irrit. 2, H315: 0,06 % ≤ C < 0,6 % Eye Irrit. 2, H319: 0,06 % ≤ C < 0,6 % Skin Sens. 1A, H317: C ≥ 0,0015 % Eye Dam. 1,, H318: C ≥ 0,6 %

(*) The complete text of the H phrases is given in section 16 of this Safety Data Sheet.

*,** See Regulation (EC) No. 1272/2008, Annex VI, section 1.2.

[1] Substance with a Community workplace exposure limit (see section 8.1).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 4 of 14

Print date: 29/10/2020

SECTION 4: FIRST AID MEASURES.

4.1 Description of first aid measures.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.

Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration.

Eye contact.

Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.

Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.

If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.

Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.

Long-term chronic exposure may result in injury to certain organs or tissues.

It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.

In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Keep the person comfortable. Turn him/her over to the left side and stay there while waiting for medical care.

SECTION 5: FIREFIGHTING MEASURES.

The product does not present any particular risk in case of fire.

5.1 Extinguishing media.

Suitable extinguishing media:

Extinguisher powder or CO₂. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:

Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.

Special risks.

Fire can cause thick, black smoke. As a result of thermal decomposition, dangerous products can form: carbon monoxide, carbon dioxide. Exposure to combustion or decomposition products can be harmful to your health.

5.3 Advice for firefighters.

Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment.

Fire protection equipment.

According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.

For exposure control and individual protection measures, see section 8.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 5 of 14

Print date: 29/10/2020

6.2 Environmental precautions.

Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.

Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.

Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations

6.4 Reference to other sections.

For exposure control and individual protection measures, see section 8.

For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.

For personal protection, see section 8.

In the application area, smoking, eating, and drinking must be prohibited.

Follow legislation on occupational health and safety.

Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.

Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25° C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorized persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m ³
diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea	330-54-1	United Kingdom [1]	Eight hours		10
			Short term		
		Éire [2]	Eight hours		10
			Short term		
Kaolin	1332-58-7	United Kingdom [1]	Eight hours		2
			Short term		
		Éire [2]	Eight hours		2
			Short term		
		United States [3] (Cal/OSHA)	Eight hours		2 (Respirable fraction) (no asbestos, < 1% crystalline silica)
			Short term		
		United States [4] (NIOSH)	Eight hours		10 (Total dust) 5 (Respirable fraction)
			Short term		
United States [5] (OSHA)	Eight hours		15 (Total dust) 5 (Respirable fraction)		

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 6 of 14

Print date: 29/10/2020

methanol	67-56-1	European Union [6]	Short term				
			Eight hours	200 (skin)	260 (skin)		
		United Kingdom [1]	Short term				
			Eight hours	200	266		
		Éire [2]	Short term				
			Eight hours	200	260		
		United States [3] (Cal/OSHA)	Short term				
			Eight hours	200			
		United States [4] (NIOSH)	Short term				
			Eight hours	250			
United States [5] (OSHA)	Short term						
	Eight hours	200	260				
ethanediol, ethylene glycol	107-21-1	European Union [6]	Short term				
			Eight hours	20 (skin)	52 (skin)		
		United Kingdom [1]	Short term				
			Eight hours	40 (skin)	104 (skin)		
		Éire [2]	Short term				
			Eight hours	20 (vapour)	10 (particulate) 52 (vapour)		
Quartz (SiO ₂)	14808-60-7	Éire [2]	Short term				
			Eight hours		0,1		
		United States [3] (Cal/OSHA)	Short term				
			Eight hours		0.05 respirable dust, 0.3 (Total Dust)		
		United States [4] (NIOSH)	Short term				
			Eight hours		Potential occupational carcinogens 0.05 respirable dust, lowest feasible concentration (LFC).		
		United States [5] (OSHA)	Short term				
			Eight hours		(Total Dust) 30 mg/m ³ /(%SiO ₂ +2)		
		sodium hydroxide, caustic soda	1310-73-2	United Kingdom [1]	Short term		
					Eight hours		2
Éire [2]	Short term						
	Eight hours				2		
United States [3] (Cal/OSHA)	Short term						
	Eight hours			(Ceiling) 2			
United States [4] (NIOSH)	Short term						
	Eight hours				(Ceiling) 2		
United States [5] (OSHA)	Short term						
	Eight hours		2				
Paraffin waxes and Hydrocarbon waxes	8002-74-2	United Kingdom [1]	Short term				
			Eight hours		2		
		Éire [2]	Short term				
			Eight hours		6		
formaldehyde	50-00-0	European Union [6]	Short term				
			Eight hours	0,3	0,37		
		United Kingdom [1]	Short term				
			Eight hours	0,6	0,74		
		Éire [2]	Short term				
			Eight hours	2	2,5		
			Short term				
			Eight hours	2	2,5		
	Short term						
	Eight hours	0,3	0,37				
	Short term						
	Eight hours	0,6	0,738				
	Short term						
	Eight hours	0.75					

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 7 of 14

Print date: 29/10/2020

		United States [3] (Cal/OSHA)	Short term	2	
		United States [4] (NIOSH)	Eight hours	Potential occupational carcinogens 0.016 (Ceiling) 0.1 [15-min] lowest feasible concentration (LFC).	
			Short term		

[1] According Limit Value (IOELV) list in 2nd Indicative Occupational Exposure adopted by Health and Safety Executive.

[2] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).

[3] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).

[4] According Compendium of Policy Documents and Statements adopted by National Institute for Occupational Safety and Health (NIOSH).

[5] According Occupational Health and Safety Standards and US Code of Federal Regulations adopted by US Occupational Safety and Health Administration (OSHA).

[6] According both Binding Occupational Exposure Limits (BOELVs) and Indicative Occupational Exposure Limits (IOELVs) adopted by Scientific Committee for Occupational Exposure Limits to Chemical Agents (SCOEL).

The product does NOT contain substances with Biological Limit Values.

Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
diuron (ISO), 3-(3,4-dichlorophenyl)-1,1-dimethylurea CAS No: 330-54-1 EC No: 206-354-4	DNEL (Workers)	Inhalation, Long-term, Systemic effects	0,17 (mg/m ³)
methanol CAS No: 67-56-1 EC No: 200-659-6	DNEL (Workers)	Inhalation, Long-term, Local effects	260 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	50 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	260 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Systemic effects	50 (mg/m ³)
	DNEL (Workers)	Dermal, Long-term, Systemic effects	40 (mg/kg bw/day)
	DNEL (General population)	Dermal, Long-term, Systemic effects	8 (mg/kg bw/day)
	DNEL (Workers)	Dermal, Acute, Systemic effects	40 (mg/kg bw/day)
	DNEL (General population)	Dermal, Acute, Systemic effects	8 (mg/kg bw/day)
ethanediol, ethylene glycol CAS No: 107-21-1 EC No: 203-473-3	DNEL (Workers)	Inhalation, Long-term, Local effects	35 (mg/m ³)
sodium hydroxide, caustic soda CAS No: 1310-73-2 EC No: 215-185-5	DNEL (Workers)	Inhalation, Long-term, Local effects	1 (mg/m ³)
	DNEL (General population)	Inhalation, Long-term, Local effects	1 (mg/m ³)
formaldehyde CAS No: 50-00-0 EC No: 200-001-8	DNEL (Workers)	Inhalation, Long-term, Local effects	0,5 (mg/m ³)
	DNEL (Workers)	Inhalation, Long-term, Systemic effects	9 (mg/m ³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.

DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

Concentration levels PNEC:

Name	Details	Value
methanol CAS No: 67-56-1 EC No: 200-659-6	aqua (freshwater)	20,8 (mg/L)
	aqua (marine water)	2,08 (mg/L)
	aqua (intermittent releases)	1540 (mg/L)
	STP	100 (mg/L)

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 8 of 14

Print date: 29/10/2020



	sediment (freshwater)	77 (mg/kg sediment dw)
	sediment (marine water)	7,7 (mg/kg sediment dw)
	soil	3,18 (mg/kg soil dw)

PNEC: Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

8.2 Exposure controls.

Measures of a technical nature:

Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	100 %				
Uses:					
Breathing protection:					
PPE:	Filter mask for protection against gases and particles.				
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.				
CEN standards:	EN 136, EN 140, EN 405				
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.				
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.				
Filter Type needed:	A2				
Hand protection:					
PPE:	Protective gloves against chemicals.				
Characteristics:	«CE» marking, category III.				
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420				
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.				
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.				
Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35
Eye protection:					
If the product is handled correctly, no individual protection equipment is necessary.					
Skin protection:					
PPE:	Protective clothing.				
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.				
CEN standards:	EN 340				
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.				
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.				
PPE:	Work footwear.				
Characteristics:	«CE» marking, category II.				
CEN standards:	EN ISO 13287, EN 20347				
Maintenance:	This product adapts to the first user's foot shape. That is why, as well as for hygienic reasons, it should not be used by other people.				
Observations:	Work footwear for professional use includes protection elements aimed at protecting users against any injury resulting from an accident				

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 9 of 14

Print date: 29/10/2020

Appearance: N.A./N.A.
Colour: N.A./N.A.
Odour: N.A./N.A.
Odour threshold: N.A./N.A.
pH: N.A./N.A.
Melting point: N.A./N.A.
Boiling Point: N.A./N.A.
Flash point: > 60 °C
Evaporation rate: N.A./N.A.
Inflammability (solid, gas): N.A./N.A.
Lower Explosive Limit: N.A./N.A.
Upper Explosive Limit: N.A./N.A.
Vapour pressure: N.A./N.A.
Vapour density: N.A./N.A.
Relative density: N.A./N.A.
Solubility: N.A./N.A.
Liposolubility: N.A./N.A.
Hydrosolubility: N.A./N.A.
Partition coefficient (n-octanol/water): N.A./N.A.
Auto-ignition temperature: N.A./N.A.
Decomposition temperature: N.A./N.A.
Viscosity: N.A./N.A.
Explosive properties: N.A./N.A.
Oxidizing properties: N.A./N.A.
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

9.2 Other information.

Dropping point: N.A./N.A.
Blink: N.A./N.A.
Kinematic viscosity: N.A./N.A.
N.A./N.A.= Not Available/Not Applicable due to the nature of the product

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.

The product does not present hazards by their reactivity.

10.2 Chemical stability.

Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.

The product does not present possibility of hazardous reactions.

10.4 Conditions to avoid.

Avoid any improper handling.

10.5 Incompatible materials.

Keep away from oxidising agents and from highly alkaline or acidic materials in order to prevent exothermic reactions.

10.6 Hazardous decomposition products.

No decomposition if used for the intended uses.

SECTION 11: TOXICOLOGICAL INFORMATION.

1-component preparations: during curing, formaldehyde is released. This can cause irreversible effects, it is a mucous membrane irritant, and it can cause skin sensitivity.

11.1 Information on toxicological effects.

Toxicological information about the substances present in the composition.

Name	Acute toxicity		
	Type	Test	Kind

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 10 of 14

Print date: 29/10/2020

methanol CAS No: 67-56-1 EC No: 200-659-6	Oral	LD50 Rat 5630 mg/kg bw [1] [1] Gigiena Truda i Professional'nye Zabolevaniya. Labor Hygiene and Occupational Diseases. Vol. 19(11), Pg. 27, 1975
	Dermal	LD50 Rabbit 15800 mg/kg bw [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974
	Inhalation	LC50 Rat 83.9 mg/l (4 h) [1] [1] Raw Material Data Handbook, Vol.1: Organic Solvents, 1974. Vol. 1, Pg. 74, 1974
sodium hydroxide, caustic soda CAS No: 1310-73-2 EC No: 215-185-5	Oral	LD50 Rabbit 325 mg/kg bw [1] [1] Naunyn-Schmiedeberg's (1937), Archiv für experimentielle Pathologie und Pharmakologie (Berlin, Germany), 184, 587-604
	Dermal	
	Inhalation	

a) acute toxicity;

Product classified:

Acute toxicity (Oral), Category 4: Harmful if swallowed.

Acute Toxicity Estimate (ATE):

Mixtures:

ATE (Dermal) = 2.096 mg/kg

ATE (Oral) = 559 mg/kg

b) skin corrosion/irritation;

Based on available data, the classification criteria are not met.

c) serious eye damage/irritation;

Based on available data, the classification criteria are not met.

d) respiratory or skin sensitisation;

Product classified:

Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;

Based on available data, the classification criteria are not met.

f) carcinogenicity;

Product classified:

Carcinogen, Category 2: Suspected of causing cancer.

g) reproductive toxicity;

Not conclusive data for classification.

h) STOT-single exposure;

Based on available data, the classification criteria are not met.

i) STOT-repeated exposure;

Based on available data, the classification criteria are not met.

j) aspiration hazard;

Not conclusive data for classification.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 11 of 14

Print date: 29/10/2020

Name	Ecotoxicity			
	Type	Test	Kind	Value
methanol CAS No: 67-56-1 EC No: 200-659-6	Fish	LC50	Trachinotus carolinus	10112 mg/L (24 h) [1] [1] Baltz, D. M. et al., Transactions of the American Fisheries Society 134: 730-740, 2005
	Aquatic invertebrates	EC50	Daphnia magna	20803 mg/L (24 h) [1] [1] Environmental Toxicology and Chemistry 14(12): 2085-2088, 1995
	Aquatic plants	EC50	Selenastrum capricornutum	22000 mg/L (96 h) [1] [1] Ecotoxicology and Environmental Safety 71: 166-1711, 2008
sodium hydroxide, caustic soda CAS No: 1310-73-2 EC No: 215-185-5	Fish	Minimal Lethal Concentration	Notropis sp.	100 mg/L (120 h) [1] [1] Van Horn et al. (1949), Effects of Kraft Mill Wastes, American Fisheries Society
	Aquatic invertebrates	LC50	Ophryotrocha diadema	33 mg/L (48 h) [1] [1] Parker JG (1984), Wat Res, 18, 865-868
	Aquatic plants			

12.2 Persistence and degradability.

No information is available regarding the biodegradability of the substances present.

No information is available on the degradability of the substances present. No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.

Information about the bioaccumulation of the substances present.

Name	Bioaccumulation			
	Log Pow	BCF	NOECs	Level
methanol CAS No: 67-56-1 EC No: 200-659-6	-0,74	-	-	Very low
ethanediol, ethylene glycol CAS No: 107-21-1 EC No: 203-473-3	-1,36	-	-	Very low
formaldehyde CAS No: 50-00-0 EC No: 200-001-8	0,35	-	-	Very low

12.4 Mobility in soil.

No information is available about the mobility in soil.

The product must not be allowed to go into sewers or waterways.

Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.

No information is available about the results of PBT and vPvB assessment of the product.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 12 of 14

Print date: 29/10/2020

12.6 Other adverse effects.

No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.

Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.

Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transportation is not dangerous. In case of road accident causing the product's spillage, proceed in accordance with point 6.

14.1 UN number.

Transportation is not dangerous.

14.2 UN proper shipping name.

Description:

ADR: Not classified as hazardous for transport.

IMDG: Not classified as hazardous for transport.

ICAO/IATA: Not classified as hazardous for transport.

14.3 Transport hazard class(es).

Transportation is not dangerous.

14.4 Packing group.

Transportation is not dangerous.

14.5 Environmental hazards.

Transportation is not dangerous.

14.6 Special precautions for user.

Transportation is not dangerous.

14.7 Transport in bulk according to Annex II of MARPOL and the IBC Code.

Transportation is not dangerous.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.

The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A

The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.

The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 13 of 14

Print date: 29/10/2020

Complete text of the H phrases that appear in section 3:

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H310	Fatal in contact with skin.
H311	Toxic in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H331	Toxic if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H350	May cause cancer.
H351	Suspected of causing cancer.
H370	Causes damage to organs.
H371	May cause damage to organs.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 2 : Acute toxicity (Dermal), Category 2
Acute Tox. 2 : Acute toxicity (Inhalation), Category 2
Acute Tox. 3 : Acute toxicity (Dermal), Category 3
Acute Tox. 3 : Acute toxicity (Inhalation), Category 3
Acute Tox. 3 : Acute toxicity (Oral), Category 3
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Carc. 1B : Carcinogen, Category 1B
Carc. 2 : Carcinogen, Category 2
Eye Dam. 1 : Serious eye damage, Category 1
Flam. Liq. 2 : Flammable liquid, Category 2
Muta. 2 : Mutagen, Category 2
Skin Corr. 1A : Skin Corrosive, Category 1A
Skin Corr. 1B : Skin Corrosive, Category 1B
Skin Corr. 1C : Skin Corrosive, Category 1C
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1A : Skin sensitiser, Category 1A
STOT RE 2 : Specific target organ toxicity following a repeated exposure, Category 2
STOT SE 1 : Specific target organ toxicity following a single exposure, Category 1

Changes regarding to the previous version:

- Change of the name of the product (SECTION 1.1).
- Change of the uses of the product (SECTION 1.2).
- Change in the hazard classification (SECTION 2.1).
- Removal of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Addition of precautionary statements/hazard statements/pictograms/signal word (SECTION 2.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Changes in the composition of the product (SECTION 3.2).
- Modifications in the first aid measures (SECTION 4.1).
- Modification of the symptoms (SECTION 4.2).
- Modifications in the handling and storage precautions (SECTION 7.1).
- Modifications in the handling and storage precautions (SECTION 7.2).
- Addition of exposure data (SECTION 8.1).
- Addition of personal protective equipment (SECTION 8.2).

-Continued on next page.-

SAFETY DATA SHEET

(in accordance with Regulation (EU) 2015/830)

VFP-27.- ANTI-MOULD ADDITIVE

Version 1 Date of compilation: 29/01/2016

Version 5 (replaces version 4)

Revision date: 23/10/2020

Page 14 of 14

Print date: 29/10/2020

- Modifications of the personal protective equipment (SECTION 8.2).
- Addition of ecotoxicity values (SECTION 11.1).
- Change in the hazard classification (SECTION 11.1).
- Addition of ecological information values (SECTION 12.1).
- Addition of ecological information values (SECTION 12.3).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).
- National legislative changes (SECTION 15.1).
- Addition of abbreviations and acronyms (SECTION 16).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:

BCF:	Bioconcentration factor.
CEN:	European Committee for Standardization.
DMEL:	Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL:	Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50:	Half maximal effective concentration.
PPE:	Personal protection equipment.
LC50:	Lethal concentration, 50%.
LD50:	Lethal dose, 50%.
Log Pow:	Logarithm of the partition octanol-water.
NOEC:	No observed effect concentration.
PNEC:	Predicted No Effect Concentration, concentration of the substance below which adverse effects are not expected in the environmental compartment.

Key literature references and sources for data:

<http://eur-lex.europa.eu/homepage.html>

<http://echa.europa.eu/>

Regulation (EU) 2015/830.

Regulation (EC) No 1907/2006.

Regulation (EU) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2015/830 of 28 May 2015 amending Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing a European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No 793/93 and Commission Regulation (EC) No 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC.

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.