



## SANIES SMOOTH

### DESCRIPTION

Rough finish coating formulated from acrylic polymers for exterior decoration and protection of facades and walls.

### ADVANTAGES

- ✓ Good breathability.
- ✓ Excellent adherence, prevents blistering on surfaces such as fibrocement, concrete, brickwork, mortar, tile, ceramics, etc.
- ✓ Weather resistant, withstands sunlight, cold and rain.
- ✓ Once dry and set, it forms a completely waterproof coat.
- ✓ Hardwearing.

### RECOMMENDED USES

Ideal for painting all types of building surfaces including facades, walls, patios, etc. Exterior and interior.

### PRESENTATION

Colours: White, with rough or smooth finish.

Finish: Matt.

5 kg and 25 kg tubs.

### TECHNICAL CHARACTERISTICS

**Composition** Fixed vehicle: Acrylic polymer resins.

Pigments: Titanium dioxide and selected extender oils.

**Density:** 1.56± 0.02 Kg/L 1.76± 0.02 Kg/L (rough finish).

**Solid volume:** 61 ± 2%.

**Coverage:** 9 – 11 m<sup>2</sup>/L per coat (Approximately, depending on surface requirements).

**Drying:** To the touch in 1 to 2 hours.  
Total 24 hours.  
Repaint After 24 hours at 20 °C.

## APPLICATION

**Coats:** 2 or more as required.

**Dilution:** 15-30 % first coat and up to 10% for successive coats.

**Application temperature:** Between 5 and 30 °C.

**Painting tools:** Spray gun, airless, wide brush, narrow brush, roller, etc.  
Shake vigorously before use.

## SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

## STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

## SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com