



PLIOLITE COATING



DESCRIPTION

Waterproofing coating formulated from Pliolite resins. Gives a smooth matt finish to every type of construction surface.

ADVANTAGES

- ✓ Excellent adherence to powdery surfaces and surfaces with poor absorption.
- ✓ Excellent weather resistance. Withstands sunlight, cold and rain.
- ✓ Once set and dry, it forms a completely waterproof breathable coat.
- ✓ Excellent wet rub resistance.

RECOMMENDED USES

Ideal for protecting and decorating facades and all types of exterior construction surfaces, even when "slightly wet" such as concrete, mortar, brickwork, stone, plaster, render and fibrocement. Its microporous structure forms a waterproof coating on exterior surfaces which require a high degree of breathability for CO₂ and water moisture.

PRESENTATION

Colour: White.

Finish: Matt

4 and 15l tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Pliolite resins.

Pigments: Titanium dioxide and selected extender oils.

Density: 1.48± 0.02 Kg/L.

Solid content: 72 ± 2%.

Coverage: 6 – 8 m²/Lt. (Approximately, depending on surface requirements).

Drying: To the touch in 1 to 2 hours

Total 24 hours

Repaint After 24 hours at 20 °C.

APPLICATION

Coats: 2 or more as required.

Dilution: 15-30 % first coat, and up to 10% in successive coats with white spirit

Application temperature: Between -10 to 35 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com