



VARNISH FOR BRICKWORK



DESCRIPTION

Water-based waterproof varnish, washable and weatherproof. Ideal for protecting natural stone, brickwork, and terracotta floor tiles, etc.

ADVANTAGES

- ✓ Penetrates the surface to form a waterproof barrier.
- ✓ The protective layer keeps out weather.
- ✓ Enhances the natural beauty of the brick and protects from scuffing.
- ✓ Moisture resistant.
- ✓ Does not yellow.

RECOMMENDED USES

Ideal for protecting natural Stone, brickwork, etc.

Use on porous surfaces. For non-porous surfaces, sand lightly or test on a small area before painting.

PRESENTATION

Colour: Colourless.

Finish: Satin (depending on the number of coats and dilution).

0.75 and 4 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle: Acrylic copolymers in emulsion.

Solvent	Water.
---------	--------

Density:	1.05 ± 0.02 Kg./L.
-----------------	--------------------

Coverage:	7 m ² /Lt.	(Depending on surface absorption).
------------------	-----------------------	------------------------------------

Drying:	to the touch	30 minutes.
	Total	3 hours.
	Repaint	After 6 hours at 20 °C.

APPLICATION

Coats: 1 or more, depending on absorption and desired finish.

Dilution: dilute with water 5-10 % for the first coat and undiluted for the second coat.

Application temperature: 5 to 30° C.

Tools: Spray gun, brush or roller.

SURFACE PREPARATION

New surfaces: must be free from dust and salt bloom, and be clean and dry.

Old surfaces: as well as the above, remove old paint. When applying over paintwork, lightly sand loose paint and fill cracks with the appropriate Pinayplast product.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com