



## ACRYLIC MORTAR



### DESCRIPTION

Acrylic mortar, durable decorative finish. Can be applied as a heavy, rustic-looking coat, ideal for exterior use. Formulated from acrylic resin.

### ADVANTAGES

- ✓ Extremely hardwearing.
- ✓ Permeable to moisture.
- ✓ Excellent weathering. Withstands sunlight, rain and cold.
- ✓ Swirly or stripped finish.
- ✓ Flexible, does not crack.
- ✓ Cracks can be filled over.
- ✓ Maximum grain size, 2mm.

### RECOMMENDED USES

Ideal for exterior walls and facades where a rustic finish is required.  
Finish: External Thermal Insulation System (ETIS).

### PRESENTATION

Colour: White and special order  
Finish: Matt.  
25 Kg tubs.

### TECHNICAL CHARACTERISTICS

**Composition** Fixed vehicle: Acrylic styrene resin.  
Pigments: Titanium dioxide and selected extender oils.

**Density:** 1.65 ± 0.02 Kg./L.

**Solid volume:** 70 ± 2%.

**Coverage:** 1-2 kg/m<sup>2</sup> (Approximately, depending on finish).

<b>Drying</b>	to the touch	1-2 hours.
	Total	24 hours.
	Repaint	After 24 hours at 20 °C.

#### APPLICATION

**Coats:** 1 or 2.

**Dilution:** Ready to use.

**Application temperature:** Between 5 and 30 °C.

Use the product as a paste, as it is, and apply with a metal float, removing excess material. Finish as required with a float. Once applied, give a final pass with plastic trowel to reduce unwanted high ridges.

#### SURFACE PREPARATION

**All new surfaces** must be dust free, clean, dry and free of salt bloom.

**For old surfaces**, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface.

#### STORAGE

Keep away from temperatures below 5 °C.

#### SAFETY

Consult the label and the Safety Data Sheet.

**Pinay**

Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com