



FLEXIBLE EXTERIOR WALLS

DESCRIPTION

Waterproof flexible coating with anti-mould additive. Excellent bonding, formulated from acrylic polymers, free of asphalt products, for waterproofing walls. ANTI-MOULD.

ADVANTAGES

- ✓ Excellent flexibility on facades to cover small and micro cracks.
- ✓ Excellent adherence, prevents blistering on surfaces such as fibrocement, concrete, brickwork, mortar, tile, ceramics, etc.
- ✓ Weather resistant, withstands sunlight, cold and rain and ozone.
- ✓ Once dry and set, it forms a completely waterproof flexible coat.
- ✓ Washable
- ✓ Breathable to prevent blistering
- ✓ Completely waterproof
- ✓ Resistant to alkalis in cement (unsaponifiable). Resistant to aggressive environments
- ✓ Non-fade colours
- ✓ Extremely resistant to wet rubbing (washable)
- ✓ Hardwearing
- ✓ Self-cleaning. Rainwater carries away dirt and dust, keeping the surface clean. Raindrops do not penetrate, and carry away dirt.

RECOMMENDED USES

Ideal for use on walls with small cracks and fissures. A solution for permeable walls, creating a permanent waterproof seal. Ideal for walls exposed to rain.

PRESENTATION

Colours: White and colour chart, base D, TR.

Finish: Matt.

4l, and 15l tub.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Acrylic polymer resins.

Additives: Water-repellent wax

Pigments: Titanium dioxide and selected extender oils.

Density: 1.35± 0.02 Kg./L.

Solid volume: 45 ± 2%

Performance: 3- 4 m²/Lt. (Approximately, depending on surface requirements).
To seal cracks measuring 0.2 to 0.3 mm, minimum consumption of 450 g/m

Drying: To the touch in 2 to 3 hours.
Total 24 hours.
Repaint After 24 hours at 20 °C.

APPLICATION

Coats: 2 or more as required.

Dilution: 15-30 % first coat and up to 10% for successive coats.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com