



PLIOLITE FIXER



DESCRIPTION

Pliolite fixer is a primer/ finish formulated from solvent-based pliolite resins to stabilise and consolidate porous and crumbling surfaces.

ADVANTAGES

- ✓ Forms waterproof barrier which penetrates the surface deeply.
- ✓ Can be applied at low temperatures.
- ✓ Excellent adherence.
- ✓ Improves adherence and controls absorption on porous surfaces.
- ✓ Ideal for exposed brickwork.

RECOMMENDED USES

Designed to stabilise and consolidate porous surfaces and powdery surfaces or those affected by lime. Use as primer for synthetic or water-based paints. Also use as varnish coat for porous surfaces needing stabilisation.

PRESENTATION

Colour: Colourless.

Finish: Semi - Matt.

0.75 L, 4 L and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle solvent-based pliolite resins.
Solvent: blended hydrocarbons.

Density: 1.10 ± 0.02 Kg/L

Coverage: 10 – 12 m²/L

Drying: To the touch 30-60 minutes.
Repaint 6 hours.

APPLICATION

Coats: 1 or 2 depending on surface and finish required.

Dilution: Ready to use.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com