



WATER-REPELLENT VARNISH



DESCRIPTION

Our water-repellent varnish treats any mineral-based building surfaces to make them water repellent and waterproof.

ADVANTAGES

- ✓ Acts as a deep-penetrating waterproof barrier.
- ✓ Protects from weather without forming a film.
- ✓ Does not affect the original colour.
- ✓ Maintains breathability.
- ✓ Produces a pearly effect, preventing the treated surface from damp.

RECOMMENDED USES

Water-repellent and waterproofing protection for concrete, render, brickwork, natural and synthetic stone, sandstone, etc.

PRESENTATION

Colour: Clear.
Finish: Matt.
0.75, 4 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Polysiloxane resin.
Solvent: Blend of hydrocarbons.

Density: 1.02 ± 0.02 Kg./L.

Solid volume: 32 ± 2%

Performance: 1.5 – 2 m²/Lt.

Drying: To the touch in 20 minutes.
Total 1 hour.
Repaint After 12 hours at 20 °C .

APPLICATION

Coats: 2

Recommended thickness: To complete impregnation.

Dilution: Ready-to-use.

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

All surfaces must be dry, sound, clean and grease-free

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com