



WATER-BASED SWIMMING POOL PAINT



DESCRIPTION

Water-based acrylic paint formulated from acrylic resin for the floor and sides of swimming pools.

ADVANTAGES

- ✓ Easy to apply.
- ✓ Excellent adherence to surface and impermeable.
- ✓ Withstands high water pressure.
- ✓ Helps cleaning and delays the formation of mould and algae.

RECOMMENDED USES

For painting the floor and walls (exterior and interior) of swimming pools built from concrete and cement.

PRESENTATION

Colours: White, blue and ocean blue.
Finish: Silk matt.
5 Kg and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle; Acrylic resins in emulsion
Pigments: Organic and non-organic
Solvent: water

Density: 1.35 Kg./L.

Coverage: 10 - 12 m²/Lt.

Drying: To the touch 30 minutes.
Repaint: 4 to 5 hours after painting.

APPLICATION

Coats: 1 or 2 depending on surface

Application temperature: 5 to 30 °C.

Painting tools: brush or roller

Wait 15 days before filling the pool.

SURFACE PREPARATION

New surfaces: wait one month before painting new construction to allow the concrete to set completely. Then wash with hydrochloric acid (Salfuman) diluted to 10% with water. Rinse well with abundant water to remove loose carbonate and sand and leave to dry completely for 48 hours. Dilute first coat with 20-25 % water and the second coat at 10 %.

Old surfaces: surfaces must be clean and free of grease. On painted pools, remove por surfaces and sand lightly well-adhered paint, and do not apply a heavy coat to these areas. Green or black staining may be the result of mould or algae and must be thoroughly cleaned before painting. Once prepared, paint according to the instructions above for new surfaces.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com