



## CHLORINATED RUBBER SWIMMING POOL PAINT



### DESCRIPTION

Chlorinated rubber pool paint for swimming pools, water tanks etc. Do not use for storing drinking water.

### ADVANTAGES

- ✓ Excellent adherence to concrete, cement and similar.
- ✓ Can be used on top of solvent-based acrylic paint.
- ✓ Impermeable to wáter.
- ✓ Excellent coverage and colour retention.
- ✓ Excellent resistance to algae formation.

### RECOMMENDED USES

For painting the floor and walls of swimming pools built from concrete and cement.

### PRESENTATION

Colours: White, blue and ocean blue  
Finish: Silk matt  
5 Kg and 15 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition:** Fixed vehicle: Chlorinated rubber resin.

Pigments: Mineral and organic

Solvent: Blend of hydrocarbons, alcohol and cetone.

---

**Density:** 1.45 ± 0.02 Kg./L.

---

**Solid volume:** 40 ± 2%.

---

**Coverage:** 12 – 13 m<sup>2</sup>/Lt. (approximately, depending on application method – spray gun per coat).

---

**Drying:** To the touch, 20 minutes.  
Total 3-4 hours.  
Repaint: 24 hours.

#### APPLICATION

**Coats:** 2

---

**Recommended thickness:** 25-30 microns per coat.

---

**Dilution:** 20 % with spray gun or airless and 5-10 % with brush or roller.

---

**Application temperature:** 5 to 30 °C.

**Painting tools:** Spray equipment, brush or roller.  
Shake well before use.  
Wait 10 to 12 days before filling pool.

#### SURFACE PREPARATION

**New surfaces:** wait one month before painting new construction to allow the concrete to set completely. Then wash with hydrochloric acid (Salfuman) diluted to 10% with water. Rinse well with abundant water to remove loose carbonate and sand and leave to dry completely for 48 hours.

**Old surfaces:** surfaces must be clean and free of grease. On painted pools, remove por surfaces and sand lightly well-adhered paint, and do not apply a heavy coat to these areas. Can be painted over and acrylic solvent-based paints can be painted over. If painting over water-based acrylic paint, test a small are beforehand for adherence.

#### STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 °C.

#### SAFETY

Consult the label and the Safety Data Sheet.

**Pinay**

Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com