



SPORTS SURFACES PAINT



DESCRIPTION

Acrylic paint for painting sports surfaces; tennis and basketball courts, etc. The paint has excellent porosity and is extremely hardwearing.

ADVANTAGES

- ✓ Excellent resistance to changing weather.
- ✓ Stable, long lasting and hard wearing.
- ✓ Easy to apply.
- ✓ Silk matt finish.
- ✓ Anti-slip finish.

RECOMMENDED USES

Ideal for sports surfaces, tarmac and walls which require an extremely hard wearing finish.

PRESENTATION

Colours: Grey, red, white, green and brown.
Finish: Matt silk.
4 and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: fixed vehicle: acrylic copolymer resins
Pigments: Mineral and organic
Solvent: water

Density: 1.45 ± 0.02 Kg./L.

Coverage: 10 – 12m²/Lt. (Depending on surface absorption).

Drying: To the touch in 1 hour.
Total 6-8 hours.
Repaint after 24 hours at 20 °C.

APPLICATION

Coats: 2

Recommended thickness: 25-30 micron per coat, dry.

Dilution: 20-30 % first coat, 10-20 % second coat. When using a spray gun dilute as necessary for optimum viscosity.

Application temperature: 5 to 30 °C.

Application tools: Brush, roller, spray gun.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom. The use of a spray gun is recommended when painting asphalt sports surfaces to prevent blocking drainage and to reduce consumption.

walls can be painted using a brush or roller.

Old surfaces: must be clean and free of dust and greas. On painted surfaces, remove old flaky paint as appropriate and avoid applying heavy coats of paint so as not to affect drainage.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com