



## EXTERIOR PLASTER



### DESCRIPTION

Plaster in powder for cement, concrete, brick, stone. Exterior or interior. Apply and sand in fine or medium-thickness coats.

### ADVANTAGES

- ✓ Fine finish.
- ✓ Excellent adherence to cement, concrete, brick, stone, etc.
- ✓ Does not run.
- ✓ Easy to prepare and apply with a trowel or float.
- ✓ Provides a fine, tough high quality finish for any type of decoration.
- ✓ Quick drying.

### RECOMMENDED USES

Ideal for exterior plastering on mineral surfaces or repairing painted walls.

### PRESENTATION

Colour: White.  
1kg, 5 kg and 15 kg sacks.

### TECHNICAL CHARACTERISTICS

<b>Composition:</b>	Water-soluble polymers and mineral content.
<b>Paste density:</b>	1.70Kg./L.
<b>Coverage:</b>	1.5Kg/ m2 and mm thick.
<b>Drying:</b>	10 hours per coat depending on thickness.
<b>Working time:</b>	2 hours depending on absorption and temperature.

## APPLICATION

**Coats:** 1 or more as necessary.

**Dilution:** One part water to two and a half parts product.

**Application temperature:** 5 to 30 °C.

## SURFACE PREPARATION

**All new surfaces** must be dust free, clean, dry and free of salt bloom.

**For old surfaces**, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be filled and levelled. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer.

## STORAGE

Keep away from temperatures below 5 °C. and damp.

## SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com