



STANDARD READY-MIXED PLASTER



DESCRIPTION

Plaster in powder for fine coats, levelling and filling cracks and small fissures.

ADVANTAGES

- ✓ Good breathability.
- ✓ Provides a fine, tough high quality finish for any type of plastic paint or wallpaper.
- ✓ Easy to prepare and apply with a trowel or float.
- ✓ Quick and easy to sand smooth.
- ✓ Reduces and equalises surface absorption, saving paint.
- ✓ Excellent adherence, quick drying.
- ✓ Minimum waste.

RECOMMENDED USES

Ideal for plastering absorbent interior walls such as plaster and plasterboard, old absorbent or matt paint, cement, concrete or wood, etc.

For levelling walls after removing wallpaper.

Fill in small imperfections, holes, cracks and dents.

PRESENTATION

Colour: White

0.35 Kg, 1 Kg, and 5 Kg tubs.

TECHNICAL CHARACTERISTICS

Composition: Water-soluble polymers and mineral content.

Paste density: 1.65Kg./L.

Coverage: 1Kg/ m² and mm thick.

Drying: 10 hours per coat depending on thickness.

Working time: 3 to 4 hours depending on absorption and temperature.

APPLICATION

Coats: 1 or more as necessary.

Dilution: One part water to three parts product.

Application temperature: 5 to 30 °C.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be filled and levelled. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer.

STORAGE

Keep away from temperatures below 5 °C. and damp.

SAFETY

Consult the label and the Safety Data Sheet.

Pinay

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com