



## PLASTER WITH FIBRE



### DESCRIPTION

Ready-mix plaster for use on cement, concrete, plaster and for sealing dynamic cracks.

### ADVANTAGES

- ✓ Flexible plaster reinforced with fibreglass.
- ✓ Does not crack or fracture.
- ✓ Excellent adherence to concrete, cement, plaster, wood and plastic paint.
- ✓ Excellent elasticity and resistance to ageing.
- ✓ Can be painted with all types of paint and waterproof coatings

### RECOMMENDED USES

Ideal for plastering and sealing interior and exterior walls small cracks and dynamic cracks. Replaces elastic tape.

### PRESENTATION

Colour: white  
1 Kg, and 5 Kg tubs.

### TECHNICAL CHARACTERISTICS

<b>Composition:</b>	Water-soluble polymers and mineral content.
<b>Paste density:</b>	1.2 Kg./L.
<b>Coverage:</b>	1Kg/ m2 and mm thick.
<b>Drying:</b>	2-8 hours per coat, depending on thickness.
<b>Working time:</b>	Unlimited.

## APPLICATION

**Coats:** 1 or more as necessary (up to 3mm per coat).

**Dilution:** One part water to three parts product.

**Application temperature:** 5 to 30 °C.

## SURFACE PREPARATION

**Fissures:** Apply with float or spatula. Press the plaster into the crack to a depth of 0.3 to 3 mm.

**Cracks:** Scrape out and remove loose material and prime with Pinay acrylic bonder or Pinay latex. Apply the product with a float or spatula in layers to prevent the formation of air bubbles. Always apply more than necessary and then level off with the spatula.

Apply in layers of 0.3 to 3 mm.

Wider, deeper cracks should be filled first with an appropriate filler.

Once set and dry, sand smooth and paint.

## STORAGE

Keep away from temperatures below 5 °C. and damp.

## SAFETY

Consult the label and the Safety Data Sheet.

The logo for Pinay, featuring the word "Pinay" in white, bold, sans-serif font on a red rectangular background.

Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com