



TIXOPÍN



DESCRIPTION

Solvent-based thixotropic paint, almost odourless. Ideal for covering difficult stains left by damp, marker pens, grease, nicotine, etc.

ADVANTAGES

- ✓ Excellent coverage, sealing and priming capabilities.
- ✓ Excellent stain sealing.
- ✓ Washable.
- ✓ Ideal for use on ceilings and walls. Does not drip or run.
- ✓ High white, does not yellow.
- ✓ Mould resistant.

RECOMMENDED USES

Formulated for kitchen ceilings and walls, bathrooms, bars, restaurants and public spaces and workshops where nicotine, grease, smoke or soot stains appear.

PRESENTATION

Colour: white.

Finish: silk matt.

0.75 L, 4 L and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Plioway resin.

Pigments: Titanium dioxide.

Solvent: Blended hydrocarbons.

Density: 1.50 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/Lt.

Drying: To the touch 30 minutes.
Total 2 hours.
Repaint after 12 hours at 20 °C.
Repaint with plastic paint 2 days.

APPLICATION

Coats 1 or 2 depending on the stain.

Dilution: 10-20 % with odourless solvent.

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery with different levels of absorption, apply a first coat diluted 35-45%, to help bonding.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com