



ANTI-HUMIDITY PAINT



DESCRIPTION

Decorative waterproofing paint, matt finish, ideal for areas where moisture is a problem

ADVANTAGES

- ✓ Easy to apply.
- ✓ Tough finish.
- ✓ Forms a barrier to prevent humidity.
- ✓ Can be applied to slightly damp surfaces.
- ✓ Excellent washability.
- ✓ Made with Pliolite resins.
- ✓ Interior and exterior use.
- ✓ Resists mould.

RECOMMENDED USES

Ideal paint for treating humidity caused by filtration and condensation.

Eliminates unsightly staining on walls

Apply to cement, plaster, stone, brickwork, etc. even if still damp. Ideal for ceilings and walls in garages, basements, car parks etc.

PRESENTATION

Colour: White.

Finish: Matt.

0.75 L, 4 L and 15 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Pliolite resin.

Pigments: titanium dioxide.

Solvent: blended hydrocarbons

Density: 1.65 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/L, single coat.

Drying: Total 1 hour.

Repaint: Min. 12 hours.

APPLICATION

Coats 1 or 2.

Dilution: 5-10 % with polyurethane solvent.

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake well before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery with different levels of absorption, apply a first coat Pinay Pliolite Bonder.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com