



PINAMAT



DESCRIPTION

High-performance plastic water-based paint formulated with acrylic resins. Excellent opacity and coverage.

ADVANTAGES

- ✓ Plastic Paint, high coverage.
- ✓ Good breathability.
- ✓ High white
- ✓ Ideal for interior decoration.
- ✓ Washable.
- ✓ Interior and exterior use.

RECOMMENDED USES

Plastic paint for painting interior walls (plaster, cement, render, etc.), ideal for good coverage on difficult surfaces (such as plasterboard) where good coverage is difficult to achieve.

PRESENTATION

Colour: white. Finish: matt.

4L and 25 Kg tubs.

TECHNICAL CHARACTERISTICS

Composition Fixed vehicle: Acrylic styrene resins

Pigments: Titanium dioxide and selected extender oils.

Density: $1.70 \pm 0.02 \text{ Kg/L}.$

Solid volume: $68 \pm 2\%$.

Coverage: 8 – 10 m2/L (Approximately).

Drying To the touch in 60 minutes.

Total 24 hours

Repaint After 24 hours at 20 °C.

APPLICATION

Coats: 2

Dilution: 15-30 % with water

Application temperature: Between 5 and 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.

Shake vigorously before use.

SURFACE PREPARATION

All new surfaces must be dust free, clean, dry and free of salt bloom.

For old surfaces, as well as the above, remove loose flaky paint. When applied over old paint, unstable or cracked surfaces must be sanded, filled and levelled with the appropriate product from the Pinayplast range. If the surface is powdery or there are differences in absorption, first apply an acrylic fixer to create a homogenous surface, particular with strong colours.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin or lumps. Keep away from temperatures below 5 $^{\circ}$ C.

SAFETY

Consult the label and the Safety Data Sheet.

