



## ANTI-RUST ENAMEL



### DESCRIPTION

A multi surface anti-rust enamel which can be painted directly onto metalwork without priming. Provides excellent resistance to weathering, adheres well to the surface and is tough and long lasting.

### ADVANTAGES

- ✓ Smooth finish.
- ✓ Apply directly to metal
- ✓ Brushes on easily.
- ✓ Excellent coverage.
- ✓ Resists exteriors well.
- ✓ Excellent anti corrosion protection.
- ✓ Multi surface adherence.

### RECOMMENDED USES

Anti-rust enamel for industrial and decorative use. Can be applied directly without priming to machinery, structures, steel bars etc.

### PRESENTATION

Colours: White and black, satin finish and from our colour chart.

Finish: Satin.

0.75 and 4 L tubs.

### TECHNICAL CHARACTERISTICS

**Composition:** Fixed vehicle – Alkaline resins.

Pigments: Selected light fast and anti-corrosion pigments.

Solvent: Blended hydrocarbons.

**Density:** 1.25 ± 0.02 Kg/L. (depending on colour).

**Solid volume:** 65-70% .

---

**Coverage:** 10 – 12 m<sup>2</sup>/Lt per coat.

**Drying:** To the touch 1 hour.  
Total 3 hours.  
Repaint 6 hours.

#### APPLICATION

**Coats:** 2

---

**Recommended thickness:** 30-35 micron, dry per coat.

---

**Dilution:** 5 % maximum with polyurethane solvent.

---

**Application temperature:** 5 to 30 °C.

---

**Painting tools:** Spray gun, airless, wide brush, narrow brush, roller, etc.  
Shake vigorously before use.

#### SURFACE PREPARATION

New surfaces: prepare adequately depending on surface  
Wood and plaster: seal first  
Metalwork and galvanised steel: no need to prime

#### STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

#### SAFETY

Consult the label and the Safety Data Sheet.

**Pinay**

Pinturas Ayelenses s.l.  
P.I. San José, s/n / 46812  
Ayelo de Malferit / Valencia / Spain  
t. 96 236 02 92 / f. 96 236 06 01  
pinturaspinay.com  
info@pinturaspinay.com