



ENAMEL FOR IRONWORK



DESCRIPTION

Metal finish synthetic enamel with excellent adherence and hard wearing colours. Gives a hammered decorative finish. Excellent exterior performance.

ADVANTAGES

- ✓ Metal finish.
- ✓ Brushes on easily.
- ✓ Hard wearing.
- ✓ Excellent coverage.
- ✓ Excellent anti-corrosion performance.

RECOMMENDED USES

Pinay ironwork enamel is ideal for painting and protecting all types of iron surfaces: handrails, bars, garden furniture and fixtures, etc.

PRESENTATION

Colours: Black, grey, brown, green, blue and gold from the automatic colour mixing system
Finish: hammered.
0.375, 0.75 and 4 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Alkaline resins.

Pigments: Selected light fast pigments.

Solvent: Blended hydrocarbons.

Density: 1.65 ± 0.02 Kg./L.

Coverage: 10 – 12 m²/Lt per coat.

Drying:

To the touch	2 hour.
Total	6 hours.
Repaint	24 hours.

APPLICATION

Coats: 2

Dilution: 5-10 % maximum with solvent for synthetic enamels.

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

New surfaces: prepare adequately depending on surface.

Wood and plaster: seal first.

Metalwork: prime with metal primer.

Galvanised steel: prime with Pinafix water or solvent-based primer.

PVC and plastic: sand lightly and prime with Pinafix solvent-based primer.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.

The logo for Pinay, featuring the word "Pinay" in a white, bold, sans-serif font on a red rectangular background.

Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com