



WATER-BASED ACRYLIC ENAMEL



DESCRIPTION

A high quality matt acrylic enamel formulated from acrylic emulsion, for painting walls.

ADVANTAGES

- ✓ High white.
- ✓ Easy to apply.
- ✓ Excellent exterior paint.
- ✓ Excellent coverage.
- ✓ Brushes on easily and smoothly.
- ✓ Excellent adherence to most surfaces (gloss and satin).
- ✓ Does not yellow.
- ✓ Odourless.

RECOMMENDED USES

A gloss or satin enamel for interior and exterior use on metal, wood and other properly prepared, sanded and primed surfaces when a high quality decorative finish is required.

PRESENTATION

Colours: white and any colour from our colour chart

Finish: matt

0.35, 0.75, 4 and 12 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Water-based acrylic resin.

Pigments: Titanium dioxide and selected extender oils.

Solvent: Water.

Density: 1.26 ± 0.02 Kg./L.

Coverage: 9– 10 m²/Lt single coat

Drying: To the touch 2 hours.
Total 24 hours.
Repaint Minimum 24 hours.

APPLICATION

Coats: 1 or 2

Dilution: 5-10 % maximum with water

Application temperature: 5 to 30 °C.

Painting tools: Spray gun, airless, wide brush, narrow brush, roller, etc.
Shake vigorously before use.

SURFACE PREPARATION

New surfaces: prepare adequately depending on surface
Wood and plaster: seal first.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com