



RUST CONVERTER



DESCRIPTION

Water-based primer to treat rust on iron and steel.
Reacts with the rust to form a layer that protects the metal underneath.

ADVANTAGES

- ✓ Transforms rust into a protective layer.
- ✓ Paint over with enamel.
- ✓ Saves sanding the entire surface, just remove flaky rust.
- ✓ Apply directly over the rust.

RECOMMENDED USES

Ideal for all types of components made from iron or steel, including window frames, doorframes, handrails and electrical appliances and vehicles.

PRESENTATION

Colour: white, turning black on reaction.
0.25 and 0.50 L tubs.

TECHNICAL CHARACTERISTICS

Density: 1.00 ± 0.02 Kg./L.

Reaction time: 15-30 minutes.

Drying: To the touch 30-45 minutes
Repaint After 6 hours (under normal temperature and humidity)

Coverage: 8-10 m² / L.

APPLICATION

Coats: 1

Dilution: Ready to use.

Application temperature: 5 to 30 °C.

Tools: Blade, brush, roller.

SURFACE PREPARATION

Remove dirt and grease before treatment by washing with warm soapy water or solvent if required, rinse and dry. Remove loose and flaky paint and rust.

How to use:

Shake well. Pour the required amount into a separate container and close the original container to protect the product's reactive qualities.

Pinay Rust Converter can be painted over rust with a brush without dilution, working it well into difficult areas. A chemical reaction will begin to appear as Rust Converter works, transforming the rust into a black layer of iron salts. If an area does not react, wash and degrease again and apply a second coat.

SAFETY

Consult label and product safety data sheet



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com