



FLOOR VARNISH



DESCRIPTION

Waterproof varnish. Highly resistant to washing and weathering, ideal for concrete driveways, industrial flooring, natural, brickwork, etc.

ADVANTAGES

- ✓ Acts as a waterproof barrier by penetrating deep into the surface.
- ✓ Protects by forming a layer against atmospheric pollution and conditions.
- ✓ Enhances the look and improves abrasion resistance.
- ✓ Resists condensation and damp.
- ✓ Does not yellow or stain

RECOMMENDED USES

Ideal for concrete driveways, industrial flooring, natural, brickwork, etc.
Can be used on porous surfaces. For non-porous surfaces, sand lightly to open the pore or test a small area first for suitability.

PRESENTATION

Colour: Clear.

Finish: Satin (depending on number of coats and dilution).

0.75 and 4 L tubs.

TECHNICAL CHARACTERISTICS

Composition: Fixed vehicle – Acrylic copolymers in emulsion.
Solvent: Water

Density: 1.05 ± 0.02 Kg/L.

Coverage: 7 m²/Lt. (Depending on surface absorption).

Drying: To the touch 30 minutes.
Total 3 hours.
Repaint: after 6 hours at 20 °C.

APPLICATION

Coats: 1 or more depending on absorption or desired finish.

Dilution: Dilute with water 30-40 % for the first coat and 20-30% for the second

Application temperature: 5 to 30 °C.

Tools: Spray gun, brush or roller.

SURFACE PREPARATION

New surfaces: must be clean, dry and free from dust and salt bloom.

Old surfaces: as well as the above, remove old paint. When applying to painted surfaces, lightly sand unsound areas and fill cracks with the appropriate Pinayplast product.

STORAGE

Easy to mix by shaking after 12 months' storage in a sealed container. Does not form skin, gel or lumps. Keep away from temperatures below 5 °C.

SAFETY

Consult the label and the Safety Data Sheet.



Pinturas Ayelenses s.l.
P.I. San José, s/n / 46812
Ayelo de Malferit / Valencia / Spain
t. 96 236 02 92 / f. 96 236 06 01
pinturaspinay.com
info@pinturaspinay.com